

»» Metropolitan Full Trip

North America's leading innovator of snow & ice control equipment!
www.vikingives.com



Reversible Plow

Standard Features:

- Eight gauge brake formed moldboard
- Top of moldboard braced with integral formed channel
- Bottom has gusseted 6" x 4" x 3/4" blade angle
- Reinforced with six plasma cut 3/8" ribs
- Enclosed trip spring canister



Options:

- ✓ Screw adjustable frame shoes
- ✓ Screw adjustable 10" caster wheels
- ✓ Various cutting edge materials
- ✓ Custom moldboard sizes
- ✓ Custom moldboard profiles (RH, LH, Double Flare)
- ✓ Moldboard & Curb shoes
- ✓ Rubber deflector
- ✓ Plow markers
- ✓ Other swivel attachments
- ✓ Various pushframe styles available



| Plow Model | Height | Path min/max | Manual Weight | PRR Weight | PRRL Weight |
|------------|------------|------------------|---------------|------------|-------------|
| R936ME | 36" | 7' 5" to 9' | 1470 | 1570 | 1590 |
| R1036ME | 36" | 8' 2 1/2" to 10' | 1570 | 1670 | 1690 |
| R1136ME | 36" | 9' to 11' | 1670 | 1770 | 1790 |
| R1142ME | 42" | 9' to 11' | 1720 | 1820 | 1840 |
| R113645ME | 36" to 45" | 9' to 11' | 1720 | 1820 | 1840 |
| R103645MEF | 36" to 45" | 8' 2 1/2" to 10' | 1620 | 1720 | 1740 |
| R113645MEF | 36" to 45" | 9' to 11' | 1690 | 1790 | 1810 |